



Peinture Cimentol  
Lionel Lassus  
ZAC de la Prévôté  
7 Route de Bû  
78550 Houdan  
France

Eurofins Product Testing A/S  
Smedeskovvej 38  
DK-8464 Galten  
Denmark

Tel. +45 70 22 42 76  
Fax +45 70 22 42 75  
ProductTesting-GA@eurofins.com  
www.eurofins.com/product-emissions

Date  
9 August 2012

Your ref.

-

Our ref.  
G17064

## Test Report – LEED 2009 EQ c4.2, SCAQMD rule 1113 (2007)

### Sample material

Sample identification	<b>EKOPUR</b>
Product type	Flat Topcoat
Product data, according to manufacturer	Density: 1.38 g/ml at 20 °C Water content: 614 g/l** Exempt compounds***.
Date received	23 July 2012
Analytical period	July to August 2012.

### Methods applied

Method	Principle	Parameter	Detection limit	Uncertainty
LEED 2009 EQ c4.2 ASTM D 2369 – 10	Gravimetric	Total Volatiles, SCAQMD rule 304	1 g/l	10 U <sub>m</sub> (%)
Volatile content of the sample was determined gravimetrically by heating up to 110 °C during 60 minutes. The result is the average of double testing. The result was calculated as: ( [g all volatiles] - [g water] - [g exempt compounds] ) / ( [l material] - [l water] - [l exempt compounds] )				

U<sub>m</sub> (%): The expanded uncertainty U<sub>m</sub> is equal to 2 x RSD%, please see [www.eurofins.dk/uncertainty](http://www.eurofins.dk/uncertainty).

### Analytical results

	<b>Solid content, % mass</b>	<b>Water content, % mass</b>	<b>VOC less water less exempt compounds, g/l</b>	<b>VOC limit g/l</b>
<b>EKOPUR SATIN</b>	59	45**	0	50 *

\* VOC limit for “Flat Topcoats”.

\*\* Given by the client

\*\*\* Not information about exempt compounds. Set to zero.

Eurofins Product Testing A/S

Thomas Neuhaus